



**GOTSCHLICH**  
DREHSPERREN



# Compact 3 Arm

## Three-Arm Turnstile

Particularly compact design, especially suitable for high-traffic, controlled outdoor access to sports and leisure facilities as well as pools and beaches.

- extra-compact design
- height-adjustable
- optional fixed-height stainless steel
- pre-assembled delivery
- noise-free operation
- unidirectional or bidirectional
- direction selectable
- high throughput
- lasting quality
- secure traffic separation
- integrated LOGITURN control
- maintenance-free
- wide range of accessories

## Functional Description:

The motorized 3-arm turnstile Compact with its rugged, all-weather powder-coated housing with integrated support is especially suitable for high-traffic, controlled outdoor access.

Ticket readers can be mounted using optional reader supports.

Compact is optionally available in stainless steel with fixed height or as Compact Plus with Designer handlebars.

A wide range of optional accessories allows adaptation to individual requirements.

## Application Areas:

- Building Access Control
- Exhibition Centers
- Event Venues / Stadiums
- Public Transport

## Technical Characteristics:

Power Supply:	230 V AC / 24V DC
Power Consumption:	max. 50 VA
Storage Temperature:	-40°C bis +40°C
Operating Temperature:	-20°C bis +50°C
Width / Lane Width:	305 mm / 577 mm
Length:	1.550 mm
Height:	1.000 - 1.365 mm
Mass:	45 kg
Material:	
Gehäuse:	Steel, powdre-coated, optionally CrNi Steel
Drehstern:	CrNi Steel Type 1.4301

## Models:

**6COM3AEB:** Compact 3-Arm height-adjustable

**6COM3AEC:** Compact 3-Arm INOX fixed height

## Extras:

**2P412-N:** Presence Sensor

**2P414-N:** Opto-sensor Release

**2P782-N:** Climb-over / Crawl-under Protection  
(monitoring of star)

**2P784-N:** Übersteigschutz  
(monitoring of lid and star)

**21769:** Red light 50 mm in Aluminum Ring

**21770:** Green light 50 mm in Aluminum Ring

**21700-N:** Reader Holder

## Suitable By-Products:

**21500K:** Palette for mobile deployment

**21510K:** Guide Rail for Palette

**8P408-N:** LOGITURN operating console

**8P407-N:** Housing for operating console

**8P409-N:** LOGITURN presettable counter

**21692:** Foundation Assembly for non-sustainable floors

